



PRICE LIST 2019

Effective 01.01.2019



Battery charger 12 volt

Page 1 HS12-15M with magnet for individual positioning

Battery charger with high-frequency technology

Page 2 HS 12/24-35

Page 2 HS 12/24-50

Page 2 HS 12/24-50D

Battery charger with multi-resonant-converter-technology (MRCT)

Page 3 HS 12/24-120

Page 3 HS 12/24-120B

Model HS12-15M

Battery charger with magnet	Price	359,00 €
	Part number	520117
		12 V 20 A with magnet for individual positioning

Characteristics HS12-15M

Battery charger 12 volt for automotive lifts and other workplaces.

Most modern high-frequency technology:
for unlimited trickle charging during service and repair

No damage to batteries

Length of cable 6 m enables the user to reach the battery at any position in the vehicle

Suitable for all current types of starter batteries
(lead-acid, gel-type, Gel, AGM, Calcium, Li-Ion)



Picture similar

Technical data HS12-15M

Nominal charging voltage	12 V
Charging current max.	15 A
Characteristic curve	I _{UoU}
Length of charging cable	6000 mm
Protection class	20 IP
Weight	2,5 kg
Dimensions (L x W x H)	177 x 104 x 55 mm
Fuse	6,3A T 250 V

Scope of delivery

Trickle charger, manual, charging cable 6m, 2 fully insulated charging clamps

Model	HS 12/24-35	HS 12/24-50	HS 12/24-50D
Battery charger with high-frequency technology	Price	585,00 €	659,00 €
	Part number	520553	520111
		12 V 24 V 35 A	12 V 24 V 50 A
			12 V 24 V 50 A

Characteristics	HS 12/24-35	HS 12/24-50	HS 12/24-50D
-----------------	-------------	-------------	--------------

Battery charger with high-frequency technology

Voltage spike-free battery charger

No damage to on-board electronic system

Suitable for all current types of starter batteries
(lead-acid, gel-type, Gel, AGM, Calcium, Li-Ion).

Carefull charging, automatic adjusting for optimal charge current



Technical data	HS 12/24-35	HS 12/24-50	HS 12/24-50D
Nominal charging voltage	12 V / 24 V	12 V / 24 V	12 V / 24 V
Charging current max.	35 A / 35 A	50 A / 50 A	50 A / 50 A
Characteristic curve	I/UoU	I/UoU	I/UoU
Length of charging cable	3000 mm	3000 mm	3000 mm
Protection class	21 IP	21 IP	21 IP
Weight	3,1 kg	3,5 kg	3,5 kg
Dimensions (L x W x H)	260 x 164 x 93 mm	260 x 164 x 113 mm	268 x 244 x 115 mm
Length of power cable	2000 mm	2000 mm	2000 mm

Scope of delivery

Battery charger, manual, charging cable, power cable, 2 fully insulated charging clamps

Model	HS 12/24-120B	HS 12/24-120
Battery charger with multi-resonant-converter-technology (MRCT)	Price 1048,00 € Part number 520598 12 V 24 V 120 A	1.335,00 € 520550 12 V 24 V 120 A

Characteristics	HS 12/24-120B	HS 12/24-120
-----------------	---------------	--------------

Battery charger with multi-resonant-converter-technology (MRCT)

Voltage spike-free battery charger for loading and flashing of vehicles

No damage to on-board electronic system

The charger ensures the operation during disconnection of the battery

Suitable for all current types of starter batteries
(lead-acid, gel-type, Gel, AGM, Calcium, Li-Ion).

Carefull charging, automatic adjusting for optimal charge current



Zubehör	HS 12/24-120B	HS 12/24-120
Carriage battery charger	Price 600,00 € Part number 520560	600,00 € 520560

Technical data	HS 12/24-120B	HS 12/24-120
Nominal charging voltage	12 V / 24 V	12 V / 24 V
Charging current max.	120 A / 60 A	120 A / 60 A
Characteristic curve	I _U U	I _U U
Length of charging cable	3000 mm	5000 mm
Protection class	21 IP	21 IP
Weight	10,0 kg	10,0 kg
Dimensions (L x W x H)	430 x 270 x 130 mm	430 x 270 x 130 mm
Length of power cable	2000 mm	5000 mm

Scope of delivery
Battery charger, manual, charging cable, power cable, 2 fully insulated charging clamps

