



# PRICE LIST 2018

Effective 01.09.2018



Trickle charger

Page 1 EL 20 M with magnet for individual positioning

Battery charger with high-frequency technology

Page 2 HS 12/24-35

Page 2 HS 12/24-50

Page 2 HS 12/24-50D

Battery charger with multi-resonant-converter-technology (MRCT)

Page 3 HS 12/24-120

Page 3 HS 12/24-120B

**Model** **EL20-M**

<b>Trickle charger with high-frequency technology</b>	Price	<b>342,00 €</b>
	Part number	520113
		<b>12 V 20 A</b>
		with magnet for individual positioning

**Characteristics** **EL20-M**

Trickle charger for automotive lifts and other workplaces.

Most modern high-frequency technology:  
for unlimited trickle charging during service and repair

No damage to batteries

Length of cable 6 m enables the user to reach the battery at any  
position in the vehicle

Suitable for all current types of starter batteries  
(lead-acid, gel-type, Gel, AGM, Calcium)



**Technical data** **EL20-M**

Nominal charging voltage	12 V
Charging current max.	20 A
Characteristic curve	IUoU
Length of charging cable	6000 mm
Protection class	20 IP
Weight	2,5 kg
Dimensions (L x W x H )	177 x 104 x 55 mm
Fuse	6,3A T 250 V

**Scope of delivery**

Trickle charger, manual, charging cable 6m, 2 fully insulated charging clamps

Model		HS 12/24-35	HS 12/24-50	HS 12/24-50D
<b>Battery charger with high-frequency technology</b>	Price	561,00 €	636,00 €	872,00 €
	Part number	520553	520111	520552
		12 V 24 V 35 A	12 V 24 V 50 A	12 V 24 V 50 A

Characteristics	HS 12/24-35	HS 12/24-50	HS 12/24-50D
-----------------	-------------	-------------	--------------

Battery charger with high-frequency technology

Voltage spike-free battery charger

No damage to on-board electronic system

Suitable for all current types of starter batteries (lead-acid, gel-type, Gel, AGM, Calcium, Li-Ion).

Carefull charging, automatic adjusting for optimal charge current



Technical data	HS 12/24-35	HS 12/24-50	HS 12/24-50D
Nominal charging voltage	12 V / 24 V	12 V / 24 V	12 V / 24 V
Charging current max.	35 A / 35 A	50 A / 50 A	50 A / 50 A
Characteristic curve	IUoU	IUoU	IUoU
Length of charging cable	3000 mm	3000 mm	3000 mm
Protection class	21 IP	21 IP	21 IP
Weight	3,1 kg	3,5 kg	3,5 kg
Dimensions (L x W x H )	260 x 164 x 93 mm	260 x 164 x 113 mm	268 x 244 x 115 mm
Length of power cable	2000 mm	2000 mm	2000 mm

#### Scope of delivery

Battery charger, manual, charging cable, power cable, 2 fully insulated charging clamps

Model	HS 12/24-120B	HS 12/24-120
<b>Battery charger with multi-resonant-converter-technology (MRCT)</b>	Price 999,00 € Part number 520598 12 V 24 V 120 A	1.297,00 € 520550 12 V 24 V 120 A

Characteristics	HS 12/24-120B	HS 12/24-120
-----------------	---------------	--------------

Battery charger with multi-resonant-converter-technology (MRCT)

Voltage spike-free battery charger for loading and flashing of vehicles

No damage to on-board electronic system

The charger ensures the operation during disconnection of the battery

Suitable for all current types of starter batteries (lead-acid, gel-type, Gel, AGM, Calcium, Li-Ion).

Carefull charging, automatic adjusting for optimal charge current



Zubehör	HS 12/24-120B	HS 12/24-120
Carriage battery charger	Price 569,00 € Part number 520560	569,00 € 520560

Technical data	HS 12/24-120B	HS 12/24-120
Nominal charging voltage	12 V / 24 V	12 V / 24 V
Charging current max.	120 A / 60 A	120 A / 60 A
Characteristic curve	I <sub>U</sub> U	I <sub>U</sub> U
Length of charging cable	3000 mm	5000 mm
Protection class	21 IP	21 IP
Weight	10,0 kg	10,0 kg
Dimensions (L x W x H )	430 x 270 x 130 mm	430 x 270 x 130 mm
Length of power cable	2000 mm	5000 mm

Scope of delivery
Battery charger, manual, charging cable, power cable, 2 fully insulated charging clamps

Technical changes reserved. Data are considered advertisement.  
Pricelist Elektron Battery Service-PL-126043-en-2018-09

